

STANDARD 6-POINT DEEP SOCKETS.



FEATURES

- **SUPER DRIVE®** design.



FEATURES

- **MADE OF NICKEL-CHROME STEEL** and mirror polished finish that prevents rust.
- **MANUFACTURED** from high-quality microalloyed steel.

ITEM	TYPE	OPENING SIZE	LENGTH	NUT END OUTSIDE DIAMETER	DRIVE END OUTSIDE DIAMETER	NUT DEPTH	
5008H	I	1/4" [6,3 mm]	2-1/2" [63,5 mm]	3/8" [9,5 mm]	11/16" [17,4 mm]	3/8" [9,5 mm]	6
5010H	I	5/16" [7,9 mm]	2-1/2" [63,5 mm]	7/16" [11,1 mm]	11/16" [17,4 mm]	5/8" [15,8 mm]	6
5012H	I	3/8" [9,5 mm]	2-1/2" [63,5 mm]	1/2" [12,7 mm]	11/16" [17,4 mm]	11/16" [17,4 mm]	6
5014H	I	7/16" [11,1 mm]	2-1/2" [63,5 mm]	5/8" [15,8 mm]	11/16" [17,4 mm]	1" [25,4 mm]	6
5016H	II	1/2" [12,7 mm]	2-1/2" [63,5 mm]	3/4" [19 mm]	3/4" [19 mm]	1" [25,4 mm]	6
5018H	II	9/16" [14,2 mm]	2-1/2" [63,5 mm]	3/4" [19 mm]	3/4" [19 mm]	1" [25,4 mm]	6
5020H	II	5/8" [15,8 mm]	2-1/2" [63,5 mm]	7/8" [22,2 mm]	7/8" [22,2 mm]	1" [25,4 mm]	6
5022H	II	11/16" [17,4 mm]	2-1/2" [63,5 mm]	15/16" [23,8 mm]	15/16" [23,8 mm]	1" [25,4 mm]	6
5024H	II	3/4" [19 mm]	2-1/2" [63,5 mm]	1-1/16" [26,9 mm]	1-1/16" [26,9 mm]	1" [25,4 mm]	6
5026H	II	13/16" [20,6 mm]	2-1/2" [63,5 mm]	1-1/8" [28,5 mm]	1-1/8" [28,5 mm]	1" [25,4 mm]	6
5028H	II	7/8" [22,2 mm]	2-1/2" [63,5 mm]	1-3/16" [30,1 mm]	1-3/16" [30,1 mm]	1" [25,4 mm]	6
5030H	II	15/16" [23,8 mm]	2-1/2" [63,5 mm]	1-1/4" [31,7 mm]	1-1/4" [31,7 mm]	1-1/16" [26,9 mm]	6
5032H	II	1" [25,4 mm]	2-1/2" [63,5 mm]	1-5/16" [33,3 mm]	1-5/16" [33,3 mm]	1-1/16" [26,9 mm]	6

