

STANDARD 12-POINT SOCKETS

SURTEK
TOOLS FOR SPECIALISTS



PROFESSIONAL
USE

100 YEARS
WARRANTY

FEATURES

● **DISEÑO**
Super Drive®.



FEATURES

● **MANUFACTURED**
from high-quality microalloyed steel.

● **NICKEL-CHROME**
plating.

ITEM	TYPE	OPENING SIZE	LENGTH	NUT END OUTSIDE DIAMETER	DRIVE END OUTSIDE DIAMETER	NUT DEPTH	
F5108	I	1/4" (6,3 mm)	1-1/8" (28,5 mm)	3/8" (9,5 mm)	5/8" (15,8 mm)	5/16" (7,9 mm)	6
F5110	I	5/16" (7,9 mm)	1-1/8" (28,5 mm)	7/16" (11,1 mm)	5/8" (15,8 mm)	5/16" (7,9 mm)	6
F5112	I	3/8" (9,5 mm)	1-1/8" (28,5 mm)	9/16" (14,2 mm)	5/8" (15,8 mm)	5/16" (7,9 mm)	6
F5114	I	7/16" (11,1 mm)	1-1/8" (28,5 mm)	9/16" (14,2 mm)	5/8" (15,8 mm)	5/16" (7,9 mm)	6
F5116	II	1/2" (12,7 mm)	1-1/8" (28,5 mm)	5/8" (15,8 mm)	5/8" (15,8 mm)	5/16" (7,9 mm)	6
F5118	II	9/16" (14,2 mm)	1-1/8" (28,5 mm)	5/8" (15,8 mm)	5/8" (15,8 mm)	7/16" (11,1 mm)	6
F5120	II	5/8" (15,8 mm)	1-3/16" (30,1 mm)	7/8" (22,2 mm)	7/8" (22,2 mm)	7/16" (11,1 mm)	6
F5122	II	11/16" (17,4 mm)	1-3/16" (30,1 mm)	15/16" (23,8 mm)	15/16" (23,8 mm)	7/16" (11,1 mm)	6
F5124	II	3/4" (19 mm)	1-3/16" (30,1 mm)	1" (25,4 mm)	1" (25,4 mm)	1/2" (12,7 mm)	6
F5126	II	13/16" (20,6 mm)	1-1/4" (31,7 mm)	1-1/16" (26,9 mm)	1-1/16" (26,9 mm)	1/2" (12,7 mm)	6
F5128	II	7/8" (22,2 mm)	1-1/4" (31,7 mm)	1-1/8" (28,5 mm)	1-1/8" (28,5 mm)	1/2" (12,7 mm)	6
F5130	II	15/16" (23,8 mm)	1-1/4" (31,7 mm)	1-1/4" (31,7 mm)	1-1/4" (31,7 mm)	1/2" (12,7 mm)	6
F5132	II	1" (25,4 mm)	1-1/4" (31,7 mm)	1-5/16" (33,3 mm)	1-5/16" (33,3 mm)	1/2" (12,7 mm)	6

