

STANDARD 6-POINT DEEP SOCKETS

SURTEK
TOOLS FOR SPECIALISTS



PROFESSIONAL
USE



FEATURES

● **SUPER DRIVE®**
design.



FEATURES

● **MADE OF NICKEL-CHROME STEEL**
and mirror polished finish that prevents rust.

● **MANUFACTURED**
from high-quality microalloyed steel.

ITEM	TYPE	OPENING SIZE	LENGTH	NUT END OUTSIDE DIAMETER	DRIVE END OUTSIDE DIAMETER	NUT DEPTH	
F5112HL	I	3/8" (9,5 mm)	2-1/2" (63,5 mm)	3/8" (9,5 mm)	3/8" (9,5 mm)	1-1/32" (26,1 mm)	6
F5114HL	I	7/16" (11,1 mm)	2-1/2" (63,5 mm)	9/16" (14,2 mm)	11/16" (17,4 mm)	1-1/32" (26,1 mm)	6
F5116HL	I	1/2" (12,7 mm)	2-1/2" (63,5 mm)	5/8" (15,8 mm)	11/16" (17,4 mm)	1-1/32" (26,1 mm)	6
F5118HL	I	9/16" (14,2 mm)	2-1/2" (63,5 mm)	31/32" (24,8 mm)	31/32" (24,8 mm)	1-1/32" (26,1 mm)	6
F5120HL	I	5/8" (15,8 mm)	2-1/2" (63,5 mm)	7/8" (22,2 mm)	7/8" (22,2 mm)	1-1/32" (26,1 mm)	6
F5122HL	I	11/16" (17,4 mm)	2-1/2" (63,5 mm)	15/16" (23,8 mm)	15/16" (23,8 mm)	1-1/32" (26,1 mm)	6
F5124HL	II	3/4" (19 mm)	2-1/2" (63,5 mm)	1-1/32" (26,1 mm)	1-1/32" (26,1 mm)	1-1/32" (26,1 mm)	6
F5126HL	II	13/16" (20,6 mm)	2-1/2" (63,5 mm)	1-3/32" (27,7 mm)	1-3/32" (27,7 mm)	1-1/32" (26,1 mm)	6
F5128HL	II	7/8" (22,2 mm)	2-1/2" (63,5 mm)	1-1/8" (28,5 mm)	1-1/8" (28,5 mm)	1-1/32" (26,1 mm)	6

