



SUPERIOR QUALITY AFFORDABLE TOOLS

ADJUSTABLE WRENCH

Handles with Rubber Grip for greater comfort.

CHROME-PLATED ADJUSTABLE WRENCHES, WITH RUBBER GRIP



the arrow indicates the turning direction.

712G


Chrome-nickel finish prevents corrosion.



795G 3-PIECE SET

WITH RUBBER GRIP HANDLE, IN POUCH

CODE	MAXIMUM OPENING		LENGTH	
	in.	mm	in.	mm
708G	1	25.4	8	203.2
710G	1 1/8	28.5	10	254.0
712G	1 5/16	33.3	12	304.8
E506	POUCH			



WITH RUBBER GRIP HANDLE											
CODE	MAXIMUM OPENING		LENGTH		JAW DEPTH		TIP THICKNESS		TORSION ENDURANCE ASME B107.8		
	in.	mm	in.	mm	in.	mm	in.	mm		gm.	lb.
704G	1/2	13	4	102	1/2	13	3/16	5	53	0.11	600
706G	15/16	24	6	152	3/4	19	7/32	6	127	0.28	1450
708G	1	25	8	203	1	25	9/32	7	254	0.56	2700
710G	1 1/8	29	10	254	1 1/8	29	5/16	8	403	0.89	4500
712G	1 5/16	33	12	305	1 5/16	33	3/8	10	700	1.54	7650
715G	1 11/16	43	15	381	1 5/8	41	5/8	16	1304	2.71	15000
718G	2 1/8	53	18	457	1 15/16	49	3/4	19	2247	4.67	20000
724G	2 7/16	62	24	610	2 7/16	62	25/32	20	3774	7.85	25000

STANDARDS: FEDERAL GGG-W-631 ASME B 107.8 NOM-0.106



the arrow indicates the turning direction.

715

Chrome-nickel finish prevents corrosion.



795 3-PIECE SET

IN POUCH

CODE	MAXIMUM OPENING		LENGTH	
	in.	mm	in.	mm
708	1	25.4	8	203.2
710	1 1/8	28.5	10	254.0
712	1 5/16	33.3	12	304.8
E506	POUCH			

CHROME-PLATED											
CODE	MAXIMUM OPENING		LENGTH		JAW DEPTH		TIP THICKNESS		TORSION ENDURANCE ASME B107.8		
	in.	mm	in.	mm	in.	mm	in.	mm		gm.	lb.
704	1/2	13	4	102	33/64	13	3/16	5	50	0.11	600
706	15/16	24	6	152	3/4	19	7/32	6	120	0.26	1450
708	1	25	8	203	1	25	9/32	7	240	0.53	2700
710	1 1/8	29	10	254	1 1/8	29	5/16	8	380	0.84	4500
712	1 5/16	33	12	305	1 5/16	33	3/8	10	660	1.45	7650
715	1 11/16	43	15	381	1 5/8	42	5/8	16	1230	2.71	15000
718	2 1/8	53	18	457	1 15/16	50	3/4	19	2120	4.67	20000
724	2 7/16	62	24	610	2 7/16	62	25/32	20	3560	7.85	25000

STANDARDS: FEDERAL GGG-W-631 ASME B 107.8 NOM-0.106